CSV SOUTHERN OCEAN

EQUIPMENT SPECIATION

GENERAL DESCRIPTION

| Туре: | Construction support vessel |
|-----------------|--|
| Classification: | DnV +1A1, DYNPOS-AUTR, EO, DK(+), CLEAN, CLEAN DESIGN, COMF-V(3), NAUT-OSV, HELDK. |
| Flag: | Malta |
| Year of Build: | 2010 |
| Builder: | Metalships & Docks, Vigo, Spain |

PRINCIPAL DIMENSIONS

| Length OA: | 136.60 m |
|------------------|----------|
| Length BP: | 120.40 m |
| Beam: | 27.00 m |
| Draft Max: | 6.85 m |
| Depth Main Deck: | 9.70 m |
| Speed | 15 knots |

MAIN DECK AREAS

| Total: | Approx 2400 m2 |
|----------------|----------------------------------|
| Deck Strength: | 10 tonnes/m ² overall |
| Deck Hatches | Two 4 x 3 m hatches |

MAIN DECK AREAS

| Main Crane: | Knuckle Jib cra | ne amidships, PS |
|------------------|----------------------------------|------------------|
| 2500 m Wire | 250 tonnes AHC @ 10 m | |
| | 75 tonnes | @ 35 m |
| Auxiliary: | 20 tonnes | @ 36 m |
| Aft. Crane: | Knuckle Jib crar | ne aftships, PS |
| 1/2 Falls | 90/110 tonnes | @ 12 m |
| 2000 m Wire | 30/30 tonnes | @ 30 m |
| Auxiliary: | 10 tonnes | @ 30 m |
| Provision crane: | S.W.L 5 Tonnes | @ 12 m |
| moon pool : | 7.2 x 7.2 m with Hatch | |
| Mooring winches: | Two off 10 tonnes | |
| Stabilising | Two passive roll reduction tanks | |
| equipment: | Two ant heeling | systems |

WATER MAKERS

```
Freshwater gen.:
```

r gen.: 2 off each 25 m² per day

HELIDECK

| 0120. | D-Value 20.88m (size 26.1m) |
|-------|---------------------------------------|
| | Suitable for Sikorsky S-92 (12.8 ton) |

| AUXILIARIES | |
|--------------------------------|--|
| Harbour generator: | Caterpillar, 580 kW |
| MAIN ENGINES | 3 |
| Number & Power: Generators: | Wartsila, 4 off, 3230 kW each 4 off 3360 kW |
| Propulsion: | Rolls-Royce, Two Azipull thrusters ea 3500kW |
| Bow Thrusters: | Rolls-Royce, One Swing-up Thruster off 1500 kW Two Tunnels off 1500 kW |

each

DYNAMIC POSITIONING SYSTEM

| Mark: | Kongsberg Maritime K-Pos 21 | |
|----------------|---------------------------------------|--|
| Class: | DnV DYNPOS-AUTR, complies NMD class 2 | |
| Reference Syst | : Two Kongsberg HiPAP 500 | |
| | Two DGPS 116/132 | |
| | LTW Taut Wire Mk15 | |
| | Fan Beam | |
| | | |

CAPACITIES

| Deadweight @ 6.85 m draft: | 10 000 tonnes |
|----------------------------|--------------------------|
| Fuel Oil: | App. 1700 m ³ |
| Portable Water: | App. 600 m ³ |
| Ballast Water: | App. 7400 m ³ |
| | |

CLIENT & OFFICE FACILITIES

| Offices and Facilites: | One Offline office on 01 ACC. |
|---------------------------|----------------------------------|
| | One online office on 04 ACC. |
| | One conference room |
| | One briefing room / cinema |
| Work shop: | One below main deck |
| Clean Power Sup.: | Sufficient UPC Systems available |

ACCOMMODATION 120 Persons

| Number of Cabins: | 50 one man and 35 two man |
|------------------------|-----------------------------|
| | one hospital with two beds. |
| Mess room: | 60 Seats |
| Recreation room: | 50 Seats |
| Conference room | 12 Seats |
| Reception room: | Reception room for helideck |
| Recreation facilities: | Gymnasium, sauna and cinema |

Specifications are subject to change without prior notice.